



SAFETY DATA SHEET

Page 1 of 2

cleaner for plastics

Revision 0
Revision date 13-Oct-2006

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name cleaner for plastics

Company Pro-Spray Automotive Finishes Ltd
Whitehall Industrial Estate
Cambridge Road
Croxtton
St Neots
PE19 6SS
Catherine@pro-spray.co.uk

Telephone +44 (0) 1480 880035

Fax +44 (0) 1480 880108

Product code icr-1333

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
1,3,5-Trimethylbenzene	1-10%	108-67-8	203-604-4	R10 Xi; R37 N; R51/53
Cumene	1-10%	98-82-8	202-704-5	R10 Xn; R65 Xi; R37 N; R51/53
1,2,4-Trimethylbenzene	10-20%	95-63-6	202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53
Low boiling point naphtha - unspecified - solvent naphtha (petroleum), light arom	20-30%	64742-95-6	265-199-0	Xi; R37-66 N; R51/53 R10-67
Low boiling point hydrogen treated naphtha - naphtha (petroleum), hydrodesulfurized heavy.	40-50%	64742-82-1	265-185-4	Xn; R65 Xi; R66 N; R51/53 R10

3. HAZARDS IDENTIFICATION

Main hazards Flammable Irritating to respiratory system. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

5. FIRE FIGHTING MEASURES

6. ACCIDENTAL RELEASE MEASURES

7. HANDLING AND STORAGE

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Cumene	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m3: 125
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m3: 250

Print date

10-Aug-2007

cleaner for plastics

Revision 0
Revision date 13-Oct-2006

9. PHYSICAL AND CHEMICAL PROPERTIES

10. STABILITY AND REACTIVITY

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

14. TRANSPORT INFORMATION

15. REGULATORY INFORMATION

Symbols

Xn - Harmful; N - Dangerous for the environment



Risk phrases

R10 - Flammable.
R37 - Irritating to respiratory system.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 - Harmful: may cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.
R67 - Vapours may cause drowsiness and dizziness.

Safety phrases

S29 - Do not empty into drains.
S62 - If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Text of risk phrases in Section 2

R10 - Flammable.
R20 - Harmful by inhalation.
R36/37/38 - Irritating to eyes, respiratory system and skin.
R37 - Irritating to respiratory system.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 - Harmful: may cause lung damage if swallowed.
R66 - Repeated exposure may cause skin dryness or cracking.
R67 - Vapours may cause drowsiness and dizziness.